

PRODUCT INFORMATION



Baton Rouge Industries, Inc.
5319 Groom Road • P.O. Box 26
Baker, Louisiana 70714
1-800-232-0334 • 225-775-3362
FX 225-775-3498
BatonRougeIndustries.com

L-605-FS 0w30 Aero Flow HD Motor Oil (Full Synthetic)

**can be used in same Dexos viscosity requirements*

01/01/18

DESCRIPTION

L-605 Full Synthetic 0W30 Motor Oil provides high quality engine protection under all driving conditions and is formulated with full synthetic base stocks and a premium additive package to provide extra protection against the harmful effects of city driving, where cars undergo a higher stress due to constant stopping and going.

L-605 Full Synthetic 0W30 Motor Oil low friction formula helps improve gas mileage for long engine life and helps protect against rust, corrosion, startup wear, varnish build-up, and eliminates the need for extra oil additives. It also protects against thermal breakdown which helps prevent stuck rings.

FEATURES/BENEFITS

- Protects engines under all driving conditions
- Lowers friction and improves gas mileage
- Provides longer engine life
- Protects against rust, corrosion and varnish
- Resists thermal break-down
- Meets GM dexos requirements

APPLICATION

L-605 Full Synthetic 0W30 Motor Oil meets requirements of API SN service. **L-605 Full Synthetic 0W30 Motor Oil** meets or exceeds the demanding requirements of International Lubricant Standardization and Approval Committee (ILSAC) GF-5, GF-4, GF-3, GF-2. ILSAC GF-5 comprises the latest standard for passenger car, van, light truck and sport utility vehicles motor oils. This product is also recommended for older engines, which owner's manual calls for API SN, SM, SL, SJ, SH, SG, SF, SE Service Classifications or any combination thereof. Viscosity recommendations vary according to temperature and engine manufacturer.

Meets the following OEM requirements:

- GM 4718M & 6094M

SAE GRADE	0W30
Specific Gravity, (60°F)	0.8295
Viscosity, Kinematic	
Viscosity, @ 40°C, cSt	69.0
Viscosity, @ 100°C, cSt	11.8
Viscosity Index	165
Cold Crank, cP @ °C, Max	5900@ -35C
Flash Point, °C (°F)	418
Pour Point, °C (°F)	-35(-40)
Noack Volatility % Max	15
Color	3.0
Zinc, wt%	0.09
Phosphorus, wt%	0.08
High Temp / High Shear Visc, cP @ 150°C,Min	2.9

SPECIFICATIONS